

DHI-VTO4202F-P

Modular Outdoor Station



Technical Specification

Model	DHI-VTO4202F-P
System	
Main Processor	SoC processor
Operating System	Embedded Linux operation system
Network Protocol	IPv4, RTSP, RTP, TCP, UDP, SIP, P2P
Basic	
Camera	CMOS Low illumination 2MP HD colorful 160° fisheye camera
Angle of View	H:160°, V:82°, D:180°
Focal Length	1.95 mm
WDR	WDR
Noise Reduction	Noise suppression and echo cancellation
Video Encoding	H.264
Frame Rate	PAL: 25 fps; NTSC: 30 fps
Video Bit Rate	256K to 2M
Light Compensation	IR light
Day/Night Switch	Yes
Audio Encoding	PCM G.711 A G.711 U
Audio Input	Built-in omnidirectional microphone
Audio Output	Built-in loudspeaker
Audio Bit Rate	16Khz 16bit
Function	
Communication Methods	Digital communication
Unlock Mode	Remote unlocking
Auto Snapshot	Yes
Leave Videos or Text Messages	Yes
Web Configuration	Yes

- Modules make the device with great expansibility
- Anodized front aluminum panel; IK07
- Supports voice and video communication
- 2 MP high definition fisheye camera with 160° view range
- Access control function; controls two locks
- Compatible with 2-wire interface and RJ45 interface
- Surface mount and flush mount
- IP65 (Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)



Performance

Housing Material	Aluminum
Port	
RS-485 Port	1 RS-485 half-duplex port
Alarm Output Port	1
Power Output Port	1-ch 12 VDC output 100mA
Unlock Button	Exit button for opening the door
Door Status Detection	Detects door magnetic status
Door Lock Control	NC/COM/NO
Ethernet Port	10/100 Mbps self-adaptive Ethernet/2-wire

Alarm

Tamper Alarm	Tamper alarm
--------------	--------------

Regular

Ingress Protection	IP65 (Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)
Appearance Color	Silver
Housing Material	Aluminum
Power Supply Mode	12 VDC/2-Wire IP Interface/PoE
Installation Method	Surface mount and flush mount
Accessory	Mounting box
Dimensions	100mm×100mm×49.30mm (3.94"×3.94"×1.94")
Protection Grade	IK07, IP65 (Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)
Working Temperature	-20°C to +60°C (-4°F to +140°F)
Working Humidity	10%RH-90%RH
Power Consumption	≤12W
Net Weight	0.35kg (0.77 lb)
Gross Weight	0.4kg (0.88 lb)

Model	DHI-VTO4202F-MB1 DHI-VTO4202F-MB2	DHI-VTO4202F-MB5	DHI-VTO4202F-MF
System			
Main Processor	Embedded MCU processor		
Capacity			
Fingerprint	-	3000	
Button			
Button Type	Mechanical button		-
Port			
Power Output Port	5V DC (Provide power for other modules)		
Regular			
Power Supply Mode	5V DC (Provided with power by other modules)		
Color	Silver		
Dimensions	100mm×49.90mm ×30.50mm (3.94"×1.96"×1.20")	100mm×100mm ×31mm (3.94"×3.94"×1.22")	100mm×100mm ×38.50mm (3.94"×3.94"×1.52")
Protection Grade	IK07; IP65 (Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)		
Operating Temperature	-20°C to +60°C (-4°F to +140°F)		
Operating Humidity	10%RH–90%RH		
Power Consumption	1W		
Appearance Color	Silver		

Model	DHI-VTO4202F-MK	DHI-VTO4202F-ML
System		
Main Processor	Embedded MCU processor	
Button		
Button Type	Metal backlight keyboard (0–9, *, #)	-
Indicator		
Indicator Lights	-	3
Port		
Power Output Port	5V DC (Provide power for other modules)	
Regular		
Power Supply Mode	5V DC (Provided with power by other modules)	
Color	Silver	
Dimensions	100mm×100mm×31mm (3.94"×3.94"×1.22")	100mm×49.90mm×28.50mm (3.94"×1.96"×1.12")
Protection Grade	IK07; IP65 (Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)	
Operating Temperature	-20°C to +60°C (-4°F to +140°F)	
Operating Humidity	10%RH–90%RH	
Power Consumption	1W	


Model	DHI-VTO4202F-MR	DHI-VTO4202F-MS
System		
Main Processor	Embedded MCU processor	
Capacity		
Card	10000	-
Display		
Display	-	3.0 inch STN display
Port		
Power Output Port	5V DC (Provide power for other modules)	
Regular		
Power Supply Mode	5V DC (Provided with power by other modules)	
Color	Silver	
Dimensions	100mm×49.90mm×28.50mm (3.94"×1.96"×1.12")	100mm×100mm×28.50mm (3.94"×3.94"×1.12")
Protection Grade	IK07; IP65 (Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)	
Operating Temperature	-20°C to +60°C (-4°F to +140°F)	
Operating Humidity	10%RH–90%RH	
Power Consumption	1W	

Model	DHI-VTO4202F-MN
Regular	
Appearance color	Silver
Dimensions	100mm×49.90mm×28.50mm(3.94"×1.96"×1.12")
Protection grade	IK07; IP65 (Apply silica gel to gaps between the device and the wall. Liquid sodium silicate is recommended. For details, see the quick start guide.)


Ordering Information

Type	Part Number	Description
Modules	DHI-VTO4202F-P	Camera module
	DHI-VTO4202F-MB1	One-button module
	DHI-VTO4202F-MB2	Two-button module
	DHI-VTO4202F-MB5	Five-button module
	DHI-VTO4202F-MS	Display module
	DHI-VTO4202F-ML	Indicator module
	DHI-VTO4202F-MK	Keyboard module
	DHI-VTO4202F-MF	Fingerprint module
	DHI-VTO4202F-MR	Card swiping module
Accessories	DHI-VTO4202F-MN	Blank Module
	VTM125	Two-modular mounting plate
	VTM126	Three-modular mounting plate
	VTM127	Two-modular mounting box
	VTM128	Three-modular mounting box


Dimensions (mm[inch])




DHI-VTO4202F-P




DHI-VTO4202F-MB1




DHI-VTO4202F-MB2




DHI-VTO4202F-MF




DHI-VTO4202F-MK




DHI-VTO4202F-ML



DHI-VTO4202F-MR



DHI-VTO4202F-MS



DHI-VTO4202F-MN

Application

