Product data sheet



FE130MS

Serratura magnetica Eco Line 300 Kgf montaggio standard.

Description

Eco Line magnetic lock 300 kgs, monitored. Surface mounting.

Application

Medium security applications for internal and external doors. To be mounted inside external doors.

Reliable Security

This state of the art electro-magnetic locking device provides positive, instantaneous door control. Filler plates, angle brackets, and other mounting adapters are available to satisfy a wide range of door and frame types and conditions.

Safe operation

Our locking devices are inherently fail-safe, releasing instantly upon command or loss of power. With no moving parts to wear, stick or bind; no mechanical linkages to bend or break; and no bolt travel time or misalignment to raise concern, both unlocking and locking are always accomplished with ease and efficiency. As those electromagnetic locking devices function independently of any mechanical type locks, magnetic locks will not jeopardize the fire door rating of an opening.



Details

- 300 kgf holding power
- Surface mounted
- No residual magnetism
- 12/24 V dc jumper selectable operation
- Monitored changeover

FE130MS

Serratura magnetica Eco Line 300 Kgf montaggio standard.

Technical specifications

Generale	
Tipo prodotto	Serrature magnetiche
Tenuta	
Forza di tenuta kgf (Forza al kilogrammo)	300 kgf
Forza di tenuta N (Newton)	3000
Monitoraggio e stato	
Monitorati	Si
Indicatore LED	Si
Interruttore stato porta	No
Passaggio monitorato	Si
Sensore magnetico	Si
Elettrico	
Valore di alimentazione	12 / 24 VDC
Consumo attuale	440 mA (+/- 2,5% @ 13,5 V)
Fisico	
Dimensioni fisiche	250 x 47 x 26 mm (W x H x D)
Colore	Alluminio
Finito	Alluminio sabbiato

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

