

# DH-HAC-HDW1500TLMQ(-A)

5MP Starlight HDCVI Quick-to-install IR Eyeball Camera



\* The parameters and datasheets below can only be applied to 1500-S2 series.

- Max 25 fps@5MP (16:9 video output)
- Quick-to-install eyeball saves installation time
- CVI/CVBS/AHD/TVI switchable
- 3.6 mm fixed lens (2.8 mm optional)
- Built-in mic(-A)
- Max. IR length 30 m, Smart IR
- IP67, 12V DC



## System Overview

Experience 5MP full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 5MP HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various motorized/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-performance make the camera an ideal choice for SMB solutions.

## Functions

### 4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio\*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

\* Audio input is available for some models of HDCVI cameras.

### Easy Installation

HDCVI Quick-to-install eyeball adopts quick-to-install pedestal, which can achieve easier installation than conventional eyeball. Quick-to-install camera reduces time and labor costs.

### Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 700 m for 5MP HD video through coaxial cable, and up to 300 m through UTP cable.\*

\*Actual results verified by real-scene testing in Dahua's test laboratory.

### Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

### Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object comes closer to the camera.

### Multi-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu. This feature makes the camera compatible with most end users' existing HD/SD DVRs.

### Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

### Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments. With working temperature range of -40 °C to +60 °C (-40 °F to +140 °F), the camera is designed for extreme temperature environments. Supporting ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4kV lightning rating provides protection against the camera and its structure from the effects of lightning.

| Technical Specification    |        |                                                                                                                                                                                                                               |                  |                  |                | WDR                                                                                                                                                                                                                                             |  | DWDR                        |  |
|----------------------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|------------------|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------------------|--|
| Camera                     |        |                                                                                                                                                                                                                               |                  |                  |                | White Balance                                                                                                                                                                                                                                   |  | Auto; manual                |  |
| Image Sensor               |        | 1/2.7 inch CMOS                                                                                                                                                                                                               |                  |                  |                | Gain Control                                                                                                                                                                                                                                    |  | Auto; manual                |  |
| Max. Resolution            |        | 2880 (H) × 1620 (V)                                                                                                                                                                                                           |                  |                  |                | Noise Reduction                                                                                                                                                                                                                                 |  | 2D NR                       |  |
| Pixel                      |        | 5MP                                                                                                                                                                                                                           |                  |                  |                | Smart IR                                                                                                                                                                                                                                        |  | Yes                         |  |
| Scanning System            |        | Progressive                                                                                                                                                                                                                   |                  |                  |                | Mirror                                                                                                                                                                                                                                          |  | Off/On                      |  |
| Electronic Shutter Speed   |        | PAL: 1/25 s–1/100,000 s<br>NTSC: 1/30 s–1/100,000 s                                                                                                                                                                           |                  |                  |                | Privacy Masking                                                                                                                                                                                                                                 |  | Off/On (8 areas, rectangle) |  |
| S/N Ratio                  |        | > 65 dB                                                                                                                                                                                                                       |                  |                  |                | Certifications                                                                                                                                                                                                                                  |  |                             |  |
| Min. Illumination          |        | 0.005 Lux/F1.6, 30IRE, 0 Lux IR on                                                                                                                                                                                            |                  |                  |                | CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014, EN 62368-1:2014+A11:2017)<br>FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014)<br>UL (UL60950-1+CAN/CSA C22.2 No.60950-1) |  |                             |  |
| Illumination Distance      |        | 30 m (98.4 ft)                                                                                                                                                                                                                |                  |                  |                | Port                                                                                                                                                                                                                                            |  |                             |  |
| Illuminator On/Off Control |        | Auto; manual                                                                                                                                                                                                                  |                  |                  |                | Audio Interface                                                                                                                                                                                                                                 |  |                             |  |
| Illuminator Number         |        | 1                                                                                                                                                                                                                             |                  |                  |                | Video Output                                                                                                                                                                                                                                    |  |                             |  |
| Pan/Tilt/Rotation Range    |        | Pan: 0°–360°<br>Tilt: 0°–78°<br>Rotation: 0°–360°                                                                                                                                                                             |                  |                  |                | One channel built-in mic (-A)                                                                                                                                                                                                                   |  |                             |  |
| Lens                       |        |                                                                                                                                                                                                                               |                  |                  |                | Power                                                                                                                                                                                                                                           |  |                             |  |
| Lens Type                  |        | Fixed-focal                                                                                                                                                                                                                   |                  |                  |                | Power Supply                                                                                                                                                                                                                                    |  |                             |  |
| Mount Type                 |        | M12                                                                                                                                                                                                                           |                  |                  |                | 12V ±30% DC                                                                                                                                                                                                                                     |  |                             |  |
| Focal Length               |        | 2.8 mm; 3.6 mm                                                                                                                                                                                                                |                  |                  |                | Power Consumption                                                                                                                                                                                                                               |  |                             |  |
| Max. Aperture              |        | F1.6                                                                                                                                                                                                                          |                  |                  |                | Max 3.2W (12V DC, IR on)                                                                                                                                                                                                                        |  |                             |  |
| Field of View              |        | 2.8 mm: 132° × 111° × 58°<br>(diagonal × horizontal × vertical)<br>3.6 mm: 109° × 92° × 48°<br>(diagonal × horizontal × vertical)                                                                                             |                  |                  |                | Environment                                                                                                                                                                                                                                     |  |                             |  |
| Iris Type                  |        | Fixed iris                                                                                                                                                                                                                    |                  |                  |                | Operating Temperature                                                                                                                                                                                                                           |  |                             |  |
| Close Focus Distance       |        | 2.8 mm: 0.9 m (3.0 ft)<br>3.6 mm: 1.6 m (5.2 ft)                                                                                                                                                                              |                  |                  |                | –40°C to +60°C (–40°F to 140°F); < 95% (non-condensation)                                                                                                                                                                                       |  |                             |  |
| DORI Distance              | Lens   | Detect                                                                                                                                                                                                                        | Observe          | Recognize        | Identify       | Storage Temperature                                                                                                                                                                                                                             |  |                             |  |
|                            | 2.8 mm | 63.6 m (208.7 ft)                                                                                                                                                                                                             | 25.4 m (83.3 ft) | 12.7 m (41.7 ft) | 6.4 m (21.0ft) | –40°C to +60°C (–40°F to 140°F); < 95% (non-condensation)                                                                                                                                                                                       |  |                             |  |
|                            | 3.6 mm | 80 m (262.5 ft)                                                                                                                                                                                                               | 32 m (105.0 ft)  | 16 m (52.5 ft)   | 8 m (26.2 ft)  | Protection Grade                                                                                                                                                                                                                                |  |                             |  |
|                            |        |                                                                                                                                                                                                                               |                  |                  |                | IP67                                                                                                                                                                                                                                            |  |                             |  |
| Structure                  |        |                                                                                                                                                                                                                               |                  |                  |                | Casing                                                                                                                                                                                                                                          |  |                             |  |
|                            |        |                                                                                                                                                                                                                               |                  |                  |                | Metal dome+metal cover+plastic decorative ring                                                                                                                                                                                                  |  |                             |  |
|                            |        |                                                                                                                                                                                                                               |                  |                  |                | Camera Dimensions                                                                                                                                                                                                                               |  |                             |  |
|                            |        |                                                                                                                                                                                                                               |                  |                  |                | φ109.9 mm × 88.1 mm ( φ4.33" × 3.47" )                                                                                                                                                                                                          |  |                             |  |
|                            |        |                                                                                                                                                                                                                               |                  |                  |                | Net Weight                                                                                                                                                                                                                                      |  |                             |  |
|                            |        |                                                                                                                                                                                                                               |                  |                  |                | 0.33 kg (0.73 lb)                                                                                                                                                                                                                               |  |                             |  |
|                            |        |                                                                                                                                                                                                                               |                  |                  |                | Gross Weight                                                                                                                                                                                                                                    |  |                             |  |
|                            |        |                                                                                                                                                                                                                               |                  |                  |                | 0.44 kg (0.97 lb)                                                                                                                                                                                                                               |  |                             |  |
| Video                      |        |                                                                                                                                                                                                                               |                  |                  |                | Frame Rate                                                                                                                                                                                                                                      |  |                             |  |
| Frame Rate                 |        | CVI:<br>PAL: 5M@25 fps; 4M@25 fps; 1080P@25 fps;<br>NTSC: 5M@25 fps; 4M@30 fps; 1080P@30 fps<br>AHD:<br>PAL: 4M@25 fps;<br>NTSC: 4M@30 fps<br>TVI:<br>PAL: 4M@25 fps;<br>NTSC: 4M@30 fps<br>CVBS:<br>PAL: 960H;<br>NTSC: 960H |                  |                  |                | Resolution                                                                                                                                                                                                                                      |  |                             |  |
| Resolution                 |        | 5M (2880 × 1620); 4M (2560 × 1440); 1080P (1920 × 1080); 960 H (960 × 576/960 × 480)                                                                                                                                          |                  |                  |                | Day/Night                                                                                                                                                                                                                                       |  |                             |  |
| Day/Night                  |        | Auto switch by ICR                                                                                                                                                                                                            |                  |                  |                | BLC                                                                                                                                                                                                                                             |  |                             |  |
| BLC                        |        | BLC/HLC/DWDR                                                                                                                                                                                                                  |                  |                  |                |                                                                                                                                                                                                                                                 |  |                             |  |

## Ordering Information

| Type        | Part Number                  | Description                                         |
|-------------|------------------------------|-----------------------------------------------------|
| 5MP Camera  | DH-HAC-HDW1500TLMQP 2.8 mm   | 5MP HDCVI IR Eyeball Camera                         |
|             | DH-HAC-HDW1500TLMQN 2.8 mm   |                                                     |
|             | DH-HAC-HDW1500TLMQP-A 2.8 mm |                                                     |
|             | DH-HAC-HDW1500TLMQN-A 2.8 mm |                                                     |
|             | DH-HAC-HDW1500TLMQP 3.6 mm   |                                                     |
|             | DH-HAC-HDW1500TLMQN 3.6 mm   |                                                     |
|             | DH-HAC-HDW1500TLMQP-A 3.6 mm |                                                     |
|             | DH-HAC-HDW1500TLMQN-A 3.6 mm |                                                     |
| Accessories | PFA13G                       | Junction Box                                        |
|             | PFB205W                      | Wall Mount Bracket (For use alone or with PFA152-E) |
|             | PFA152-E                     | Pole Mount Bracket (For use with PFB205W)           |
|             | PFA130-E                     | IP66 Junction Box                                   |
|             | PFM800-4K                    | Passive HDCVI Balun                                 |
|             | PFM321D                      | 12V 1A Power Adapter                                |
|             | PFM904                       | Integrated Mount Tester                             |

## Accessories

### Optional:



PFA13G  
Junction Box



PFB205W  
Wall Mount Bracket  
(For use alone or with  
PFA152-E)



PFA152-E  
Pole Mount Bracket  
(For use with PFB204W)



PFA130-E  
IP66 Junction Box




PFM800-4K  
Passive HDCVI Balun



PFM321D  
12V 1A Power Adapter



PFM904  
Integrated Mount Tester



## Dimensions (mm[inch])

