

ASR1101M ASR1101M-D

Vandal-proof RFID Reader



Technical Specification

Mode	ASR1101M	ASR1101M-D
------	----------	------------

System

Main Processor	8 Bit
----------------	-------

Read

Read Format	13.56MHz	125KHz
Read Range	1cm–3cm (max.)	
Reading time	<0.1s	

Function

Tamper Alarm	Yes
--------------	-----

Interface

To Controller	RS485, Wiegand34(Wiegand 26 optional)
---------------	---------------------------------------

General

Keyboard	12Key(0-9, *, #), number key 5 is a braille button
LED Indicator	Blue backlight
Beep Tone	Buzzer
Ingress protection	IK08
Power Supply	9V–15V DC/100mA
Operating Temperature	-30°C to +60°C
Working Humidity	≤95%
Dimension(W×D×H)	110mm×85mm×26mm
Weight	0.5kg
Working Environment	Indoor

Certificates

CE	Yes
FCC	Yes

Features

- Support RS485, Wiegand34 protocol(Wiegand 26 optional)
- 13.56MHz(Mifare)
- 125KHz(EM-ID)
- All-metal buttons with blue backlight
- Red and Green indicator LEDs
- Watch dog function ensure device free from halting
- Surface mounted installation



Dimensions

