

WA-AB_06-100/T-EN54

Diffusore da parete A/B 2 x 6 W

Product overview

The WA-AB 06-100/T-EN54V is designed with two independent speakers and 100 V transformers to enable an economic operation of two separated speaker lines (A/B-lines) for highest security demands. In case of a failure of one speaker line the redundancy of the chassis and the transformers will guarantee unimpaired function. Excellent qualified for the installation in sports facilities and schools. The speaker is also compliant with the British Standard BS 5839, Part 8. The 2 x 6 W powered speaker is equipped with two full-range loudspeakers and two 100 V transformer with 3 power adjustments, each. The high-density, shock-resistant MDF wood housing in white provides a low resonance sound. A sturdy front grille made of steel guarantees enduring stability. For additional reliability, a 2-pin-ceramic block, thermal fuses are provided and the speaker chassis are impregnated against wetness.

The speaker is also secured with the high protection class IP54 against the security risks of environmental influences. Quick and easy mounting with screws.



Details

- Wall-mounted AB (2 lines) speaker 2 x 6 W

WA-AB_06-100/T-EN54

Diffusore da parete A/B 2 x 6 W

Technical specifications

Elettrico

Consumo di energia	2 x 6 W
Livello di uscita	85 dB

Fisico

Dimensioni fisiche	252 x 194 x 82 mm (W x H x D)
Peso netto	2.24 kg
Colore	Bianco (RAL 9010)
Tipo di montaggio	Montaggio a parete
Posizione di montaggio	Parete

Ambientale

Temperatura operativa	-10 to +55°C
IP rating	IP54

Standard e norme

Standards	EN54-24
-----------	---------



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 6 September 2021 - 11:42