

DH-PFS3008-8GT-L

8-Port Desktop Gigabit Ethernet Switch



- Compact design: Miniature size and light weight make it easy to deploy
- Plug and play: No configuration required
- Green technology: Adopts high quality environmentally friendly plastics
- 7x24H: Stable performance for long-term operation

System Overview

8 × 10/100/1000 Mbps adaptive ports, highly integrated design, compact, portable, easy to operate, suitable for small and medium office and home networks.

Technical Specification

Performance

Layer	Layer 2
Managed	No

Hardware

Standard Power Supply	Yes
PoE	No
Ethernet Port	8
Ethernet Port Rate	1 Gbps
Power Supply	5V/1A DC
Operating Temperature	-10°C to 55°C (14°F to 131°F)
Operating Humidity	10%–90%
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
Storage Humidity	10%–90%
Power Consumption	Idling: 0.81W Full load: 4W

Performance

Switching Capacity	16 Gbps
Packet Forwarding Rate	11.9 Mpps
Packet Buffer Memory	1.5 Mbits
MAC Table Size	2K
Standards Compliance	IEEE 802.3i, IEEE 802.3u, IEEE802.3ab, IEEE802.3x

Application

The product is applicable to small and medium office and home networks.

General

ESD	Air discharge: 8kV Contact discharge: 4kV
Thunderproof	Common mode: 2kV
Net Weight	0.11 kg (0.24 lb)
Gross Weight	0.22 kg (0.49 lb)
Dimensions	125 mm × 65 mm × 22 mm (4.92" × 2.56" × 0.87")
Packaging Dimensions	128 mm × 77 mm × 78 mm (5.04" × 3.03" × 3.07")

Dimensions (mm[inch])

