

TVTH-S01-0003-TUR-G

TruVision IP thermal turret camera, 256 × 192, 7 mm lens, 4MP Visible Light Camera

Overview

TruVision S series IP thermal Cameras is the answer for demanding customers to detect unwanted activities in difficult weather or light conditions. The thermal IP camera line-up is accessible and offers advanced features to ensure precision for your customer's optimal security.

The cameras go above and beyond standard motion detection with enhanced alarm capabilities, including cross line detection, intrusion detection and region entrance/exit features. With its smart person/vehicle feature the camera can ignore irrelevant motion or VCA events which will automatically lead to less storage consumption and faster retrieval of relevant video events.

TruVision S series IP thermal Cameras utilize H.265 and/or H.264 compression technology with triple-streaming capability, making it easy to manage the camera's bandwidth usage. Recording to a local MicroSD card (not included) protects data in the event of network disruptions.

TruVision S series IP thermal Cameras can be used in combination with a variety of TruVision recording platforms, as well as any third party platform using ONVIF connectivity.

Why choose the S series of thermal IP cameras?

Our new range of thermal cameras can be integrated in the full Aritech ecosystem. With the recorders, the network products, TruVision Navigator, it completes the full Carrier security network.



Details

- Bi-Spectral (thermal and optical)
- Uncooled thermal sensor
- 4MP Optical camera (side by side)
- H.265 compression
- Intelligent VCA human and vehicle detection
- Long range object detection
- IP66 rating for outdoor installation
- Embedded analytics for perimeter protection application
- PoE+ support
- SD card support for edge recording
- ONVIF Profile G, S, T open standards

TVTH-S01-0003-TUR-G

TruVision IP thermal turret camera, 256 × 192, 7 mm lens, 4MP Visible Light Camera

Technical specifications

Generale

Technology	IP, Thermal
OSD	Picture Overlay, Text Overlay
Modalità di visualizzazione	Mirror, OSD, OSD with custom text overlays, ROI (Region Of Interest)
Compatibilità Software	TruVision Navigator, TVRmobile, Web Browser

Telecamera

Pixels totali (H x V)	256 x 192
-----------------------	-----------

Codifica

Video streams	3
Compressione flusso principale	H.264, H.265
Compressione flusso secondario	H.264, H.265, MJPEG
Compressione del terzo flusso	H.264, H.265, MJPEG
Risoluzione flusso principale	1280 x 720 (XVGA), 320 x 240 (QVGA), 640 x 480 (VGA), 704 x 576 (4CIF)
Risoluzioni flusso secondario	320 x 240 (QVGA), 640 x 480 (VGA), 704 x 576 (4CIF)
Risoluzione del terzo flusso	320 x 240 (QVGA), 640 x 480 (VGA), 704 x 576 (4CIF)
Risoluzione Max. @ fps	1280 × 720 @ 25 fps

Obiettivo

Tipo obiettivo	Fixed
Lunghezza focale	7 mm
f-stop	f1.0

Network

Integration	ONVIF
Protocolli di rete supportati	802.1x, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, PPPoE, QoS, RTP, RTSP, SMTP, SNMP, TCP, UDP

Audio

Compressione audio	G.711a, G.711u, G.722, G.726
Audio in	1 Mic in/Line in interface, line input: 2-2.4V[p-p]; output impedance: 1KΩ, ±10%
Audio out	1 Audio output interface, line level, impedance: 600Ω

Allarme I/O

Ingresso di allarme	2
Uscita di allarme	2

Memoria

Supporto registrazione locale	Si
Local storage type	Micro SD/SDHC/SDXC
Capacità Max. di registrazione	Up to 128GB

Intelligenza Video

Analisi video	Intrusion detection, Rilevazione Line crossing, Rilevazione entrata in regione, Rilevazione uscita da regione
Intelligence options	VCA human and vehicle detection

Elettrico

Tensione di esercizio	12VDC PoE (802.3af, class 3)
Consumo di energia	7W (Max)

Fisico

Dimensioni fisiche	321 mm × 106 mm × 107 mm
Peso netto	1.55 kg
Colore	Grey
Form Factor	Turret

Ambientale

Ambiente	Interno / Esterno
Temperatura operativa	-40°C to 65°C
Umidità relativa	90% or less, no condensation
IP rating	IP66

Normative

Conformità	CE, cUL, REACH, RoHS, UKCA, UL, WEEE
------------	--------------------------------------

Camera

Image sensor	Vanadium Oxide Uncooled Focal Plane Arrays
IFOV	1.74 mrad
Pixel Interval	12 μm
NETD	≤ 40 mK (25°C), F1.0
Minimum focal distance	1.3 m
Maximum detection range	up to 881 m (vehicle) / 287 m (human)
Maximum recognition range	uo to 220 m (vehicle) / 72 m (human)
Maximum identification range	up to 110 m (vehicle) / 36 m (human)
VCA Range for Vehicles	up to 144 m (4.0 x 1.4 m)
VCA Range for Humans	up to 55 m (1.8 x 0.5 m)
Temperature Measurement Range	up to 116 m (1 x 1 m)
Temperature Measurement Range	up to 23 m (0.2 x 0.2 m)

Optical Camera

Image Sensor	1/2.7" Progressive Scan CMOS
Total Effective Pixels	2688 x 1520
Shutter Time	1 s to 1/100,000 s
WDR	120 dB
Day/Night	True Day/Night (with motorised IR cut filter)
Color sensitivity	Color: 0.0176 Lux @ (F2.25, AGC ON), B/W: 0.0035 Lux @ (F2.25, AGC ON)
Focal Length	6.4 mm
IR Range	Up to 15 m

TVTH-S01-0003-TUR-G

TruVision IP thermal turret camera, 256 × 192, 7 mm lens, 4MP Visible Light Camera

Lens

Field of View	24.9° (H) × 18.7° (V)
---------------	-----------------------

Accessories

TVD-BB3	TruVision dome back box
TVD-M2-WM	TruVision Indoor wall mount

Alarm I/O

Visual Alarm	Yes. White light flashing alarm
Audio alarm	Yes, for two types of audible alarm (VCA and Temperature Exception). 2 preset voice alerts (one for each). 6 importable user-defined voice alerts (6 options shared in the two types)

Video intelligence

VCA	4 VCA rule types (line crossing, intrusion, region entrance, and region exiting), up to 8 VCA rules in total.
Temperature Measurement	3 temperature measurement rule types, 21 rules in total (10 points, 10 areas, and 1 line)
Temperature Range	- 20 to 150°C
Temperature Accuracy	± 8°C



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 5 May 2022 - 13:31