

DHI-LM22-L200

22" FHD Monitor



Features:

- · Light and cost-effective plastic housing
- · Support 7*24 operation
- \cdot High fidelity digital processing for a brilliant and vivid video
- · Fast response time with no image blurring or ghosting
- · Low energy consumption, long service life

Technical Specification

M	O	d	e	
VΙ	O	a	е	

Model	DHI-LM22-L200
Display	
Screen Size	22"
Panel type	VA
Aspect Ratio	16:9
Resolution	1920*1080
Backlight	ELED
Brightness/Luminance	200cd/m²
Contrast Ratio	3000:1
Display Color	16.7M
Viewing Angle(H/V)	178°(H)/178°(V)
Response time	6.5ms
Refresh Rate	75Hz
Signals	
Input	VGA×1, HDMI×1
General	
Power Supply	DC 12V, 2A

Consumption (Standard)	20W				
Consumption (Standby)	≤0.5W				
Net Weight	2.5kg				
Gross Weight	3.4kg				
Bezel Width	17.4mm(U), 16.2mm(R/L), 20.9mm(B)				
VESA	75×75mm				
Dimension without base (W×H×D)	n without base (W×H×D) 509.9x307.4x37.5mm				
Package(W×H×D)	565x115x371 mm				
Work Environment	Temperature	0°C~40°C (32°F~104°F)			
work environment	Humidity	10%~85%			
Accessory					
Standard	HDMI Cable, Power Adapter, Base				
Certifications					
Certifications	CE/FCC				

Rev 002.000