

ATS1500A-IP-MM-HK

Kit composto da centrale Advisor Advanced 8-32 zone, 4 aree, in contenitore metallico con comunicatore IP integrato ATS1500A-IP-MM e dalla tastiera con lettore di prossimità integrato

Intrusion alarm system

Advisor Advanced is a full-blown security solution that is combining intrusion and access control together with state-of-the-art connectivity solutions, satisfying a wide range of remote applications.

The product family has 3 variants and depending on the variant supporting between 32 and 512 zones that can be configure for 4 to 64 independent areas. Zones may be assigned to a specific area (offices, stores,...) or common to all (entrance area, reception,...). Each area can have a separate User Interface.

The Advisor Advanced product line is designed and tested to be fully compliant to EN50131, Security grade 2 or grade 3 depending on the product and the housing variant.

Advisor Advanced product line

Advisor Advanced product line is a family of several types of control panels (ATSx500A series) that have the same software, menu structure and basic methods of interacting with users. Using existing ATS accessories such as keypads, readers and expanders, it delivers a reliable system and a large range of options to extend the functionality of the system.

Ease of use

The Advisor Advanced system is designed to provide "ease of use". The Advisor Advanced range offers easy menu access and menu browsing as well as quick-access to menu items. Hints are available to provide help during configuration. The use of regular functions, such as set and unset, are designed to be intuitive to end-users.

Wireless and wired sensor support

The Advisor Advanced system is a full hybrid system. It allows for connection of any combination of wired and wireless sensors.

Communication


Advisor Advanced provides flexible communication options, such as wireless communications, with or without IP on board or optional GSM, GPRS, 3G or 4G and PSTN. The ATSx500A-IP platform has an integrated 10/100 Mb Ethernet connection supporting IP reporting to OH-NETREC receiver and U/D functionality to ATS85x0 downloaders. Connection to the UltraSync is provided through onboard IP or through ATS73xx range GPRS/3G/4G devices.

Remote FW upgrade

Firmware upgrades can be performed using USB stick without need of a pc or remotely, drastically reducing the number of required site visits and therefore cost (as of firmware MR3.0).

Remote & mobile solutions

Security systems are very often connected to Alarm monitoring centres



Details

- 8 onboard zone inputs
- Max 32 zones: wired, wireless or mixed
- Economic input and output plug-in expansion
- Up to 16 shock sensor inputs
- 4 areas
- Up to 2000 users without access controller and up to 65532 with access controller
- USB port for local configuration
- Plug-on PSTN dialler for reporting or configuration included
- Multilingual - own language for each user
- IP Alarm reporting to OH-NETREC receiver - Optional GPRS/3G/4G
- Integrated 10/100 Mb Ethernet connection
- Standard access control without additional door controllers
- Full access control using CDC4 door controllers
- Auto Arming - Schedules - Times Outputs
- Live and scheduled Panel Health Check through UltraSync for registered systems

that 24 hours per day monitor for alarms and initiate response to events requiring this. These may also provide other services, such as performing health check and remote servicing. The Advisor Advanced ATS85xx remote service software is built to equip monitoring operators with the tools to service multiple events and panels, and to help them improve service levels for professional customers.

End users can benefit from the ATS8600 Advisor Management solution, that integrates intrusion, access, video and fire in one single software package.

End users can also monitor and control their system via the mobile app supported for IOS and Android and receive push messages. Alarms are received when they occur, event logs can be reviewed, and action can be taken.

Integrated Access Control

All Advisor Advanced panels provide integrated access can control where end-user can be grouped. Each group has a separate definition for doors accessible as well as when access is allowed. Being a truly integrated system, additionally users can disarm areas when access to a door is granted.

Advisor Advanced can be expanded with more advanced access control functionalities like anti-passback or lift control using the CDC4 four to eight door and lift controller. This way up to 96 intelligent doors can be controlled. The door controllers are designed to continue full operation when the network to the computer or Advisor Advanced may be interrupted.

UltraSync cloud solution

Advisor Advanced starting from firmware version MR4.0 supports the UltraSync cloud solution. End-users can benefit from the UltraSync connectivity services by connecting mobile apps that provide alarm monitoring and control of their alarm system. Installers can benefit from this too. All their Advisor Advanced panels connected to UltraSync they can quickly connect to from any location for configuration and diagnostics using ATS85xx downloaders. UltraSync does not require configuration of home routers, knowledge of IP addresses and does not require DDNS services. For alarm reporting to Alarm Receiving Centers, UltraSync provides a reliable method to deliver any event.

ATS1500A-IP-MM-HK

Kit composto da centrale Advisor Advanced 8-32 zone, 4 aree, in contenitore metallico con comunicatore IP integrato ATS1500A-IP-MM e dalla tastiera con lettore di prossimità integrato

Technical specifications

Sistema

Linee prodotto	Advisor Advanced
Tipo prodotto	Controllo Accessi Integrato
Tipo di centrale	Ibrido
Kit	Si
Numero di tastiere/lettori	8
Data Gathering Panels (DGP)	7
Numero di gruppi di allarmi	16
Cavo specifico	WCAT52 / WCAT54 or equivalent

Ingressi

No. Max di ingressi	32
Ingressi a bordo	8
Ingressi espansione plug-8 in	

Uscite

No. di uscite	128
Numero di uscite a bordo	5

Area

Numero di aree	4
----------------	---

Utente/carte

Numero massimo di utenti	more than 2000
Utenti con nome	1000
Numero massimo di tessere	2000 to 65532
Numero massimo di codici PIN	2000 to 65532

Controllo accessi

Porte standard in centrale	4
Gruppi di porte	128
Gruppi di piani	128
Porte intelligenti su DGP a 4 porte	28

Comunicazioni

Tipo di trasmissione a bordo	IP
Estensione di trasmissione	GSM, GSM/GPRS, GSM/GPRS/IP, PSTN
Tipo di databus	RS485

Registro eventi

Registro degli eventi di allarme	14500
Accesso al registro degli eventi	10000

Elettrico

Tipo di alimentatore	230 VAC
Valore di alimentazione	230 VAC +10%, -15%, 50/60 Hz
Consumo corrente scheda madre	150 mA
Corrente massima di sistema	950 mA at 13.8 V \pm 0.2 V
Max corrente aux	750 mA (depends on backup power needs)
Ripristino automatico dei fusibili	5
Fusibili per rottura vetri	1 (mains power)

Fisico

Dimensioni fisiche	315 x 388 x 85 mm
Materiale	Acciaio (verniciato)
Custodia	Metallico Medio

Ambientale

Temperatura operativa	-10 to +55°C
Umidità relativa	95% noncondensing
Classe ambientale	Class II, indoor
IP rating	IP30

Regulatory

Grado EN50131	Grade 3, with tamper kit
Conformità	CE



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 5 May 2023 - 9:36