

TX-2511-03-1

Sensore a doppia tecnologia, 12 metri, 868 MHz Gen2 immune ai piccoli animali domestici

One way transmitter

The sensor has a chip tuned wireless transmitter that communicates with a 868AM Gen2 receiver such as, for example the ATS1235.

The learn-in process of the sensor is identical to the process used with legacy sensors.

Each sensor reports a unique ID code with each transmission.

The sensor also reports the battery and transmitter condition (supervisory signal) to the panel every 18 minutes.

Patented Range Gated Radar Technology

This series of wireless motion sensors incorporate a UTC Fire & Security patented and unique range gated radar technology allowing the installer to define a clear borderline of the radar range as the radar is used to measure distance between the sensor and moving objects. Effectively the end-user will get rid of any nuisance alarms generated by movements outside the detection range.

Every motion sensor comes with four possible radar ranges selectable via jumpers allowing the detection range to be tailored according to the room where the motion sensor is installed.

The radar operates on 5.8GHz frequency and will not interfere with any WiFi networks.

PIR combined with mirror power

The patented optical mirror technology gives the advantage of gliding focus, which creates a volumetric detection curtain from floor level up to installation height resulting in a sensor that never loses track of the object.

In these series we are using a dual element digital pyro generating two volumetric curtains for each of the nine curtain sets.

Detection technologies working together

These dual tech motion sensors generate an alarm depending on what both technologies – range gated radar and PIR – saw within their detection coverage.

But our dual tech go beyond a simple “AND” function : it classifies the signals from each technology – range gated radar and PIR – to have the best alarm result without being sensitive for nuisance signal sources. This technology creates a uniform sensitivity in all course directions.

Ease and flexibility of installation

- 1.Easy opening and closing system.
- 2.Easy access when changing the batteries.
- 3.Easy access to mirror optics.
- 4.Tolerates wall angle deviation and different mounting heights.
- 5.One mounting plate for all sensors in the series.

Other members of the family

This family includes motion sensors with variants in detection ranges



Details

- Patented selectable range gated radar technology clearly defining the radar detection border
- PIR technology with patented mirror curtain optics
- Intelligent alarm decision based on signal classification of the PIR and radar alarm
- Full under-crawl detection
- No adjustment required for different mounting heights
- Tolerates wall angle deviation
- End-user friendly product design for exchanging batteries
- 3-years battery life with 2 batteries
- PetImmune functionality
- Holding several security approvals (pending)

and a Pet Immune variant.

The consistent family aesthetics between the various models ensure a professional approach when installing different sensor types.

TX-2511-03-1

Sensore a doppia tecnologia, 12 metri, 868 MHz Gen2 immune ai piccoli animali domestici

Spécifications techniques

Généralités

Tecnologia	Doppia tecnologia
Tipo di applicazione	Wall mount
Antimascheramento	No
Immune ad animali	Si
Telecamera	No
Tempo di avvio del rivelatore	1 minute

Détection

Campo massimo di rilevamento	12 m
Selezione dell'intervallo di rilevamento	4, 6, 9 and 12 m
Numero di tende	9
Copertura (campo visivo)	86°
Frequenza microonda (nom.)	5.8 GHz
Protezione antistrisciamento	Si
Velocità obiettivo	0.3 m/s to 3 m/s

Filaire-Radio

Cablaggio-wireless	Senza fili
Frequenza Wireless	868 MHz AM

Électrique

Consumo attuale	58 µA (average), 50 mA (max.)
Batterie	2 x 3.0 V (1300 mAh lithium)
Durata della batteria	3 anni

Caractéristiques physiques

Dimensioni fisiche	130 x 69 x 53 mm
Peso netto	176 g (including two batteries)
Colore	Bianco
Altezza di montaggio	2.3 to 3 m, EN 2.3 to 2.6 m

Environnement

Temperatura operativa	-10 to 55° C
Umidità relativa	95% max. condensing
Ambiente	Interno
IP rating	IP30 / IK02

Regulatory

Grado EN50131	Grade 2
---------------	---------



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 5 May 2023 - 9:38