

DH-SD42C212T-HN

2MP 12x Starlight PTZ Network Camera



- 1/2.8" 2Megapixel STARVIS™ CMOS
- Powerful 12x optical zoom
- Support Triple-streams encoding
- Max. 25/30fps@1080P
- IVS
- Support PoE+
- IK10



System Overview

Featuring powerful optical zoom and accurate pan/tilt/zoom performance, the camera provides a wide monitoring range and great detail. The camera delivers 1080P resolution at 25/30fps. The camera is equipped with smooth control, high quality image, and good protection, meeting compact size demands of video surveillance applications.

Functions

Starlight Technology

For challenging low-light applications, Dahua's Starlight Ultra-low Light Technology offers best-in-class light sensitivity, capturing color details in low light down to 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, resulting in clear images in dark environments.

Wide Dynamic Range

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Smart H.265+

Smart H.265+ is the optimized implementation of the H.265 codec that uses a scene-adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction to deliver high-quality video without straining the network. Smart H.265+ technology reduces bit rate and storage requirements by up to 70% when compared to standard H.265 video compression.

PFA Technology

PFA technology has innovatively introduced new methods of judgment to ensure the accuracy and predictability of the direction of subject distance adjustment. The result is a set of advanced focusing algorithms. PFA ensures clarity of the image throughout the process of zooming and shortens focus time. The realization of PFA technology substantially improves user experience and increases product value.

Environmental

Dahua cameras operate in extreme temperature environments, rated for use in temperatures from -30 °C to +60 °C (-22 °F to +140 °F) with 90% humidity. The camera complies with the IK10 Vandal Resistance impact rating.

Protection

The camera allows for ±10% input voltage tolerance, suitable for the unstable conditions for outdoor applications. Its 2KV lightning rating provides effective protection for both the camera and its structure against lightning.

Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

Technical Specification			
Camera			
Image Sensor		1/2.8” STARVIS™ CMOS	
Effective Pixels		1920(H) x 1080(V), 2 Megapixels	
RAM/ROM		1024M/128M	
Scanning System		Progressive	
Electronic Shutter Speed		1/1s~1/30,000s	
Minimum Illumination		Color: 0.005Lux@F1.6; B/W: 0.0005Lux@F1.6	
IR Distance		N/A	
IR On/Off Control		N/A	
IR LEDs		N/A	
Lens			
Focal Length		5.3mm~64mm	
Max. Aperture		F1.6 ~ F4.4	
Angle of View		H: 58.2° ~ 4.8°	
Optical Zoom		12x	
Focus Control		Auto/Manual	
Close Focus Distance		100mm~ 1000mm	
DORI Distance			
*Note: The DORI distance is a “general proximity” of distance which makes it easy to pinpoint the right camera for your needs. The DORI distance is calculated based on sensor specification and lab test result according to EN 62676-4 which defines the criteria for Detect, Observe, Recognize and Identify respectively.			
Detect	Observe	Recognize	Identify
883m(2897ft)	353m(1158ft)	177m(581ft)	88m(289ft)
PTZ			
Pan/Tilt Range		Pan: 0° ~ 360° endless; Tilt: -2° ~ 90°,auto flip 180°	
Manual Control Speed		Pan: 0.1° ~300° /s; Tilt: 0.1° ~120° /s	
Preset Speed		Pan: 300° /s; Tilt: 200° /s	
Presets		300	
PTZ Mode		5 Pattern, 8 Tour, Auto Pan ,Auto Scan	
Speed Setup		Human-oriented focal Length/ speed adaptation	
Power up Action		Auto restore to previous PTZ and lens status after power failure	
Idle Motion		Activate Preset/ Scan/ Tour/ Pattern if there is no command in the specified period	
Protocol		DH-SD	
Intelligence			
Event Trigger		Motion detection, Video tampering, Network disconnection, IP address conflict, Illegal access, Storage anomaly	
Auto Tracking		N/A	
IVS		Tripwire, Intrusion,Abandoned/Missing	

Advanced Intelligent Functions	Face Detection
Video	
Compression	H.265+/H.265/H.264+/H.264/MJPEG(Sub Stream)
Streaming Capability	3 Streams
Resolution	1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480)/CIF(352×288/352×240)
Frame Rate	Main stream: 1080P/720P(1 ~ 25/30fps)
	Sub stream1: D1/CIF(1 ~ 25/30fps)
	Sub stream2: 720P/D1/CIF(1 ~ 25/30fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.265/H.264: 448K ~ 8192Kbps
Day/Night	Auto(ICR) / Color / B/W
Backlight Compensation	BLC / HLC / WDR(120dB)
White Balance	Auto, ATW, Indoor, Outdoor, Manual
Gain Control	Auto / Manual
Noise Reduction	Ultra DNR (2D/3D)
Motion Detection	Support
Region of Interest	Support
Electronic Image Stabilization (EIS)	N/A
Defog	Support
Digital Zoom	16x
Flip	180°
Privacy Masking	Up to 24 areas
Audio	
Compression	G.711a/G.711Mu/G.726/AAC
Network	
Ethernet	RJ-45 (10XBase-T/100Base-TX)
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,PPPOE,DDNS,FTP, IP Filter,QoS,Bonjour,802.1x
Interoperability	ONVIF Profile S&G, API
Streaming Method	Unicast / Multicast
Max. User Access	20 users
Edge Storage	NAS (Network Attached Storage),Local PC for instant recording, Micro SD card 256GB
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	Smart PSS, DSS, DMSS
Smart Phone	IOS, Android
Certifications	
Certifications	CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB,ANSI C63.4- 2014 UL: UL60950-1+CAN/CSA C22.2,No.60950-1

Interface	
Video Interface	N/A
RS485	N/A
Audio I/O	1/1
Alarm I/O	2/1
Electrical	
Power Supply	DC 24V/2.5A(±25%), PoE+(802.3at)
Power Consumption	12W
Environmental	
Operating Conditions	-30°C ~ 60°C (-22°F ~ +140°F) / Less than 90% RH
Ingress Protection	N/A
Vandal Resistance	IK10
Construction	
Casing	Metal
Dimensions	Φ198(mm)×158(mm)
Net Weight	2.3kg(5.07lb)
Gross Weight	3.3kg(7.28lb)

Ordering Information		
Type	Part Number	Description
2MP PTZ Camera	DH-SD42C212T-HN	2MP 12x Starlight PTZ Network Camera, WDR, PAL
	DH-SD42C212TN-HN	2MP 12x Starlight PTZ Network Camera, WDR, NTSC
	SD42C212T-HN	2MP 12x Starlight PTZ Network Camera, WDR, PAL
	SD42C212TN-HN	2MP 12x Starlight PTZ Network Camera, WDR, NTSC
Accessories	DC24V/2.5A	Power Adapter

Accessories

Included:



DC24V/2.5A
 Power Adapter

Dimensions (mm)

