

DP991

Rivelatore ottico di fumo Apollo Discovery (58000-600)

General

The DP991 is an elegant, slim-line, optical sensor with high performance analogue addressable features. Compensation for sensor drift is included as part of the internal signal-processing algorithm.

Optical smoke monitor

The optical smoke detectors has an internal pulsing LED and a photo-diode at an obtuse angle. In clear air conditions the photo-diode in the monitor receives no light from the LED and produces a corresponding analogue signal. This signal increases when smoke enters the chamber and light is scattered onto the photodiode. The signal is processed by the electronic circuitry and transmitted to the control equipment in exactly the same way as in the case of the ionisation smoke monitor.

Drift compensation

The drift compensation algorithm will compensate for changes in sensor output caused, for example, by dust in the chamber, and will therefore hold the sensitivity at a constant level even with severe chamber contamination. This increased stability is achieved without significantly affecting the detector's sensitivity to fire.

Compensation values are stored in nonvolatile memory and will be retained even if detectors are disconnected.

Unique addressing

A unique, patented addressing method provides simple, user-friendly and accurate identification of monitor location whereby a coded card, inserted in the base, is read by any monitor as it is plugged in. All the electronic components are in the monitor, but the location information is held in the base. Addressing errors during maintenance and service are eliminated. Precoded and pre-numbered address cards are also available. These address cards simplify and speed up installation and commissioning.



Dettagli

- 5 Approved response modes for ease of optimisation to different environments
- Rejection of transient signals
- Drift compensation to ensure constant sensitivity
- 360° Alarm visibility
- Flashing LED option
- Fast alarm reporting
- EN54 approved and CPR certified

DP991

Rivelatore ottico di fumo Apollo Discovery (58000-600)

Specifiche tecniche

Generale	
Indicazione stato	2 clear LEDs (red in alarm)
Compatibilità	Addressable panels with 900 series (Apollo) support
Livelli di allarme	5
Connettività	2-wire loop
Metodo di indirizzamento	Indirizzamento tessere

Elettrico	
Tipo di alimentatore	Alimentato ad anello
Tensione di esercizio	17 to 28 VDC
Comunicazione	5 to 9 V (peak to peak)
Consumo attuale	300 µA (quiescent) 3.5 mA (alarm)

Rivelazione	
Principio di rilevamento	Optical light scatter
Monitoraggio	Alarm threshold, Contamination level
Velocità aria	No effect

Uscita	
Quantità in uscita	1
Tipo di uscita e intervallo	Remote LED output (<5 mA)
Programmabile	Yes

Fisico	
Dimensioni fisiche	100 x 42 mm (Ø x H)
Peso netto	105 g
Colore	Bianco
Tipo di montaggio	Montaggio su base
Materiale (scatola)	Polycarbonato

Ambientale	
A prova di vandalo	No
Temperatura operativa	-20 to +60°C
Temperatura di immagazzinamento	-40 to +70°C
Umidità relativa	0 to 95% noncondensing
Ambiente	Interno
IP rating	IP44

Regolatorio	
Conformità	CE, REACH, RoHS 3, WEEE
Certificazioni	CPR
Standards	EN54:7