

SC-43-0200-0001-99

SmartCell Contact Transmitter and Input Device for Information Zones

Overview

The SmartCell Input Device is quick and easy to install and offers individual addressing at the SmartCell Control Panel. The device allows non fire to be monitored at the SmartCell Control Panel and to an information alert when activated. Examples may include the monitoring of doors (opening/closing), a loss of power to your fridge, flood detection and an alarm condition on your intruder system.

Features include a resistor monitored input, an alternative magnetic contact option and bidirectional 868 MHz communication.

This device is third party certified and compatible with the full SmartCell product range.



Dettagli

- Full wireless communication with panel
- Quick and easy to install
- Resistor monitored input
- Alternative magnetic contact option (magnet supplied)
- For connection to remote information devices
- NOT FOR FIRE OR SECURITY APPLICATIONS

SC-43-0200-0001-99

SmartCell Contact Transmitter and Input Device for Information Zones

Specifiche tecniche

Generale

Frequenza Wireless	868 MHz
--------------------	---------

Ingresso

Quantità in entrata	1
Tipo di input e intervallo	Resistor monitored input

Fisico

Dimensioni fisiche	30 x 110 x 28 mm (W x H x D)
Peso netto	0.05 kg
Colore	Bianco
Tipo di montaggio	Montaggio a parete
Batterie	1 x ER14505M 3.6 V lithium thionyl chloride battery (Fanso or Titus)

Ambientale

Temperatura operativa	-10 to +55°C
Temperatura di immagazzinamento	-10 to +30°C (with battery) -10 to +55°C (without battery)
Umidità relativa	95% noncondensing max.
Ambiente	Interno

Regolatorio

Conformità	CE
Standards	R&TTE



In quanto azienda in continua innovazione, Carrier Fire & Security si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 11 January 2024 - 12:56