

IM1640PAG

Surface mount contact, armoured cable, NFA2P

Commercial surface mount contact

The IM1640 series commercial surface mount contacts are specifically designed to work on metal frames. The contacts can be used in harsh environments. Special version with armoured cable and including junction box is available.



Dettagli

- Designed for use in harsh environments
- Magnet specifically designed to work on metal frames
- Tamper loop
- Version with armoured cable

IM1640PAG

Surface mount contact, armoured cable, NFA2P

Specifiche tecniche

Generale

Tipo di applicazione	Montaggio a superficie
Tipo contatto	NC
Connettività	4 wires, 60 cm (armoured cable)

Cablato / senza fili

Cablato / senza fili	Cablato
Gap operativo	25 mm

Elettrico

Tensione	max. 48 VDC
----------	-------------

Fisico

Dimensioni fisiche	72 x 23 x 19 mm (W x H x D)
Dimensioni magneti	23 x 72 mm
Dimensioni contatto/sensore	23 x 72 mm
Colore	Bianco

Ambientale

Temperatura operativa	-10 to +55°C
-----------------------	--------------



In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.

Last updated on 9 July 2025 - 17:32