

# R1125TW-N

## Stubby press-fit recessed mount contact with terminals and "Mini-Max" magnet, wide gap

## Stubby "Press-Fit" contact

The Sentrol R1125T series "Stubby" Press-Fit magnetic contacts are a 9 mm switch designed specifically for applications where space is limited. The short length makes it ideal for thin-framed windows and doors where longer units cannot be used. Press fit ribs on the housing make for quick, easy installation. The Mini-Max magnet can be fitted where almost no space is available to mount a normal magnet.

#### **Easy installation**

Switch is hermetically sealed reed switch, which is potted using exclusive polyurethane potting compound into the switch housing. Switch is drill-mounted in wood or aluminum with a suitable adhesive. The Alnico V Mini-Max magnet mounts with adhesive take or a stainless steel screw. The switch housing has three fins to press-fit against the mounting hole.

#### **Durability and dependability**

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.

#### High quality components and materials

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.





#### Dettagli


- · Rare-earth magnet technology delivers powerful magnetic force
- Ideal for PVC windows and doors
- Easy to install in any situation
- Magnet mounts easily with glue, double-sided tape, or stainless-steel screw

# R1125TW-N

# Stubby press-fit recessed mount contact with terminals and "Mini-Max" magnet, wide gap

## Specifiche tecniche

Generale	
Tipo di applicazione	Montaggio ad incasso
Tipo contatto	NC
Connettività	2 x screw term.
Cablato / senza fili	
Cablato / senza fili	Cablato
Gap operativo	22 mm
Fisico	
Dimensioni magnete	16 x 3 mm (Ø x L)
Dimensioni	9 x 27 mm (Ø x L)
contatto/sensore	
Diametro	9 mm
Colore	Bianco





In quanto azienda in continua innovazione, Kidde Global Solutions si riserva il diritto di modificare le specifiche del prodotto senza preavviso. Per avere informazioni sempre aggiornate, visita it.firesecurityproducts.com online o contatta il tuo riferimento commerciale.