

# GS300

**Sensore piezo rottura vetri mini con memoria.**

## High Performance

---

The glassbreak detector GS300 is designed to detect the specific ultrasonic frequency range produced by breaking glass. Knocks and other normal disturbances to a windowpane do not trigger an alarm. Suitable for use on standard window glass or plate glass the GS300 provide a 2 meter radius of protection. The detector may be fitted as close as 2 cm from the window frame and still provide a full 2 metre radius of coverage on standard glass. The detector is moulded into a plastic housing and delivered with 2m cable as a standard (exists also in 6 & 20 meters). They are featuring a built-in latch LED indicator for easy location of alarmed detectors.



## Dettagli

---

- Small and unobtrusive
- Latching alarm indication
- 2m radius protection
- Easy to install
- No adjustment
- Tamper proof

# GS300

Sensore piezo rottura vetri mini con memoria.

## Specifiche tecniche

### Generale

|                               |            |
|-------------------------------|------------|
| Tecnologia                    | Piezo      |
| Tipo di vetro                 | Piato      |
| Gamma                         | 2 m radius |
| Interruttore antimanomissione | No         |

### Cablato / senza fili

|                      |         |
|----------------------|---------|
| Cablato / senza fili | Cablato |
|----------------------|---------|

### Elettrico

|                    |                               |
|--------------------|-------------------------------|
| Power supply value | 3 to 16 VDC                   |
| Consumo attuale    | 4 mA @ 6 VDC<br>9 mA @ 12 VDC |

### Fisico

|                    |                        |
|--------------------|------------------------|
| Dimensioni fisiche | 37 x 19 x 12 mm        |
| Peso netto         | 50 g                   |
| Colore             | Bianco                 |
| Tipo di montaggio  | Montaggio a superficie |

### Ambientale

|                       |              |
|-----------------------|--------------|
| Temperatura operativa | -25 to +70°C |
| IP rating             | IP67         |

### Regolatorio

|                |                      |
|----------------|----------------------|
| Certificazioni | EN50131 Grade 2, VdS |
|----------------|----------------------|