

IO950NI

Apollo IO Unit (SA4700-102)

General

IO950NI is the new input/output unit which provides supervision of one or more normally open contacts connected to a single pair of cables and a set of changeover relay output contacts.

Mechanical Construction

The IO950NI is available in the new faceplate style enclosure. It is designed to be surface mounted to the wall and consists of 3 parts:

- a back box with knock-outs for cable entry
- a PCB assembly
- a protective front cover

Ease of Installation

Improved design for ease of wiring meaning faster installation – unit can be fitted to back-box before wiring is connected. Colour coded terminal blocks for easier identification (green for loop wiring, yellow for mains wiring, grey for inputs and low voltage relays).



Dettagli

- Improved design for ease of wiring meaning faster installation
- Loop powered
- Supervise one or more NO switches on a single cable pair
- Local LEDs signalling I/O and fault conditions
- Isolators within each device

IO950NI

Apollo IO Unit (SA4700-102)

Specifiche tecniche

Elettrico

Tensione di esercizio	17 to 35 VDC
Consumo attuale	0.9 mA (Power-up surge) 0.5 mA (Quiescent) 0.5 mA max. (LEDs disabled) 3.5 mA max. (Alarm LEDs On)

Fisico

Dimensioni fisiche	150 x 90 x 60 mm
Peso netto	244 g

Ambientale

Temperatura operativa	-40 to +70°C
Umidità relativa	0 to 95% noncondensing
Ambiente	Interno

Regolatorio

Certificazioni	CPR, EN54-17, EN54-18
----------------	-----------------------

Electrical

Protocol voltage	5 t o 13 V peak-to-peak
------------------	-------------------------