

DT992

Sensore termico con uscita remota o.c. - EN54.

General

The DT992 is an elegant, slim-line addressable heat detector that provides temperature information to the CIE. It uses a single thermistor to sense the air temperature around the detector. With its 5 operating modes, it supports 5 classes of temperature detectors as stipulated by EN54.

Operating Modes

Every operating mode has a different behaviour, each suitable for a different application. All modes have a fixed temperature trigger, with optional rate-of-rise selection allowing the detector to respond to a temperature alarm before the fixed level is reached. The DT992 supports A1R (57°C with rate-of-rise), A2R (61°C with rate-of-rise), A2S (61°C static), CR (90°C with rate-of-rise) and CS (90°C static) modes of operation.

Unique Addressing

A unique, patented addressing method provides simple, user-friendly and accurate identification of device location. A coded card, inserted in the base, is read by the detector as it is plugged in. All the electronic components are in the detector, but the location information is held in the base. Addressing errors during maintenance are eliminated because the address remains in the base. Pre-coded and pre-numbered address cards are available.

Applications

The DT992 is ideal for use in environments that are dirty or smoky under normal conditions. It is therefore well suited installation in warehouses, loading bays and car parks.



Dettagli

- 5 Approved response modes for ease of optimisation to different environments
- Rejection of transient signals
- Drift compensation to ensure constant sensitivity
- 360° Alarm visibility
- Flashing LED option
- Fast alarm reporting
- EN54 approved and CPR certified

DT992

Sensore termico con uscita remota o.c. - EN54.

Specifiche tecniche

Generale

Indicazione stato	Alarm: Dual Red LEDs
-------------------	----------------------

Elettrico

Tensione di esercizio	17 to 28 VDC
Consumo attuale	3.5 mA (Alarm) 400 µA (Quiescent)

Fisico

Dimensioni fisiche	100 x 42 mm (Ø x H)
Peso netto	105 g
Colore	Bianco
Tipo di montaggio	Montaggio su base
Materiale (scatola)	Polycarbonato

Ambientale

Temperatura operativa	-40 to +80°C (Operating mode dependent)
Temperatura di immagazzinamento	-40 to +80°C
Umidità relativa	0 to 95% noncondensing
Ambiente	Interno
IP rating	IP54

Regolatorio

Certificazioni	EN54-5
----------------	--------

Electrical

Communication voltage (peak to peak)	5 to 9 V
Remote LED output	<5 mA

Environmental

Max. wind (continuous)	Not affected
------------------------	--------------